## **Andy Tiernan Classics**

## The Old Railway Station Framlingham Suffolk IP13 9EE Tel 01728 724321

Used Antique Motorcycle Brief Evaluation Report						2/03/2023	Tester AMC	
Make BSA	Model M21		<b>Year</b> 1959		Reg No WYY 345		Oils checked E, G, P	
<b>Price £</b> 5,000	Colour Maroon &		k cream	Stock No 08451BSA			<b>cc</b> 600	
VIN/Frame BM20S.12388		Location LH	Location LHS lower headstock			Engine No BM21.12702.		
Registration Documents: DVLA V5C registration document							MOT expiry Exempt	
History. This bike has been part of Andy's personal collection since 2011								

Headlamp Operation       ✓       Image: Constraint of the second					
NeuronVStop lamp OperationVHorn OperationVHorn OperationVBatteryVVoltage = 6Earth polarity = Pos.ForksVForksVSwing Arm Bearingsn/aWheel AlignmentVGirder Links If Applicablen/aFront BrakeVControls Clevis Pins etcVFront Tyre tread depthVSize 3.25 x 19(See note 3 below) AvonFront BearingsVFront BearingsVFront Rear BrakeVFront BearingsVFront BearingsVFront BearingsVFront Rear BearingsVFront SpokesVFront SpokesV					
Charging System Operation $\checkmark$ Voltage = 6Earth polarity = Pos.Fuse fittedBattery $\checkmark$ Voltage = 6Earth polarity = Pos.Fuse fittedHead Bearings $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Forks $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Swing Arm Bearingsn/a $\checkmark$ $\checkmark$ Wheel Alignment $\checkmark$ $\checkmark$ $\checkmark$ Girder Links If Applicablen/a $\checkmark$ $\checkmark$ Front Brake $\checkmark$ $\checkmark$ $\checkmark$ Rear Brake $\checkmark$ $\checkmark$ $\checkmark$ Controls Clevis Pins etc $\checkmark$ $\checkmark$ Front Tyre tread depth $\checkmark$ Size 3.25 x 19Front Bearings $\checkmark$ $\checkmark$ Rear Tyre tread depth $\checkmark$ Size 3.50 x 19Front Bearings $\checkmark$ $\checkmark$ Front Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$ Plating = 95%					
Charging System Operation $\checkmark$ Voltage = 6Earth polarity = Pos.Fuse fittedBattery $\checkmark$ Voltage = 6Earth polarity = Pos.Fuse fittedHead Bearings $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Forks $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Swing Arm Bearings $n/a$ $\checkmark$ $\checkmark$ Wheel Alignment $\checkmark$ $\checkmark$ $\checkmark$ Girder Links If Applicable $n/a$ $\checkmark$ Front Brake $\checkmark$ $\checkmark$ Rear Brake $\checkmark$ $\checkmark$ Controls Clevis Pins etc $\checkmark$ $\checkmark$ Front Tyre tread depth $\checkmark$ Size $3.25 \times 19$ Front Bearings $\checkmark$ $\checkmark$ Rear Braings $\checkmark$ $\checkmark$ Front Rim $\checkmark$ Size $3.50 \times 19$ Rear Bearings $\checkmark$ $\checkmark$ Front Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$ Plating = 95%					
Charging System Operation $\checkmark$ Voltage = 6Earth polarity = Pos.Fuse fittedBattery $\checkmark$ Voltage = 6Earth polarity = Pos.Fuse fittedHead Bearings $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Forks $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Swing Arm Bearingsn/a $\checkmark$ $\checkmark$ Wheel Alignment $\checkmark$ $\checkmark$ $\checkmark$ Girder Links If Applicablen/a $\checkmark$ $\checkmark$ Front Brake $\checkmark$ $\checkmark$ $\checkmark$ Rear Brake $\checkmark$ $\checkmark$ $\checkmark$ Controls Clevis Pins etc $\checkmark$ $\checkmark$ Front Tyre tread depth $\checkmark$ Size 3.25 x 19Front Bearings $\checkmark$ $\checkmark$ Rear Tyre tread depth $\checkmark$ Size 3.50 x 19Front Bearings $\checkmark$ $\checkmark$ Front Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$ Plating = 95%					
Battery       Voltage = 0       plantify = 105.       plast fitted         Head Bearings $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Forks $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Swing Arm Bearings $n/a$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Wheel Alignment $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Brake $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Rear Brake $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Sclevis Pins etc $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Tyre tread depth $\checkmark$ Size 3.25 x 19       (See note 3 below) Avon $\checkmark$ Front Bearings $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Rim $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Rim $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Spokes $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ $\checkmark$ Front Spokes $\checkmark$ $\checkmark$					
SectorFront Brake $\checkmark$ Image: Sector					
Girder Links If Applicable $n/a$ Front Brake $\checkmark$ Rear Brake $\checkmark$ Controls Clevis Pins etc $\checkmark$ Front Tyre tread depth $\checkmark$ Size $3.25 \times 19$ (See note 3 below) AvonRear Tyre tread depth $\checkmark$ Front Bearings $\checkmark$ Rear Bearings $\checkmark$ Front Rim $\checkmark$ Rear Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$					
Girder Links If Applicable $n/a$ Front Brake $\checkmark$ Rear Brake $\checkmark$ Controls Clevis Pins etc $\checkmark$ Front Tyre tread depth $\checkmark$ Size $3.25 \times 19$ (See note 3 below) AvonRear Tyre tread depth $\checkmark$ Front Bearings $\checkmark$ Rear Bearings $\checkmark$ Front Rim $\checkmark$ Rear Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$					
Girder Links If Applicable $n/a$ Front Brake $\checkmark$ Rear Brake $\checkmark$ Controls Clevis Pins etc $\checkmark$ Front Tyre tread depth $\checkmark$ Size $3.25 \times 19$ (See note 3 below) AvonRear Tyre tread depth $\checkmark$ Front Bearings $\checkmark$ Rear Bearings $\checkmark$ Front Rim $\checkmark$ Rear Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$					
Front Brake $\checkmark$ Rear Brake $\checkmark$ Controls Clevis Pins etc $\checkmark$ Front Tyre tread depth $\checkmark$ Size 3.25 x 19(See note 3 below) AvonRear Tyre tread depth $\checkmark$ Front Bearings $\checkmark$ Front Bearings $\checkmark$ Rear Bearings $\checkmark$ Front Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$					
Rear Brake $\checkmark$ Rear Brake $\checkmark$ Controls Clevis Pins etc $\checkmark$ Front Tyre tread depth $\checkmark$ Size 3.25 x 19(See note 3 below) AvonRear Tyre tread depth $\checkmark$ Front Bearings $\checkmark$ Rear Bearings $\checkmark$ Front Rim $\checkmark$ Rear Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$					
Front Tyre tread depth       ✓       Size 3.25 x 19       (See note 3 below) Avon         Rear Tyre tread depth       ✓       Size 3.50 x 19       (See note 3 below) Avon         Front Bearings       ✓       Size 3.50 x 19       (See note 3 below) Avon         Front Bearings       ✓       Plating = 95%         Rear Rim       ✓       Plating = 95%         Front Spokes       ✓       Plating = 95%					
Front Tyre tread depth       ✓       Size 3.25 x 19       (See note 3 below) Avon         Rear Tyre tread depth       ✓       Size 3.50 x 19       (See note 3 below) Avon         Front Bearings       ✓       Size 3.50 x 19       (See note 3 below) Avon         Front Bearings       ✓       Plating = 95%         Rear Rim       ✓       Plating = 95%         Front Spokes       ✓       Plating = 95%					
Rear Tyre tread depth $\checkmark$ Size $3.25 \times 19$ (See note $3$ below) AvonFront Bearings $\checkmark$ Rear Bearings $\checkmark$ Front Rim $\checkmark$ Rear Rim $\checkmark$ Front Spokes $\checkmark$					
Front Bearings $\checkmark$ Plating = 95%       Front Rim $\checkmark$ Plating = 95%       Front Spokes $\checkmark$					
Rear Bearings $\checkmark$ Rear Rim $\checkmark$ Front Spokes $\checkmark$					
Front Rim $\checkmark$ Plating = 95%       Rear Rim $\checkmark$ Plating = 95%       Front Spokes $\checkmark$					
Rear Rim $\checkmark$ Plating = 95%Front Spokes $\checkmark$					
Front Spokes					
Deep Service					
Rear Spokes 🗸					
Exhaust Silencers $\checkmark$ Plating = 95%					
Exhaust Pipes $\checkmark$ Plating = 90%					
Fuel System Leaks					
Speedo $\checkmark$ Reading = 28342					
Cables 🗸					
Handle bars/Levers $\checkmark$ Plating = 95%					
Final Drive Chain					
Primary Chain Tension     ✓       Engine Condition     ✓					
Engine Condition					
Cold Starting					
Hot Starting					
Oil Leaks The odd drip under the engine					
Gearbox operation ✓ No of gears 4					
Clutch operation $\checkmark$					
Road Test Evaluation ✓ Distance covered 4 miles	Distance covered 4 miles				
Carburettor $\checkmark$ Type = Amal MonoblocTester reportsStarted readily from cold $\ell$ bet. The motor reports well calling strengty from low rays. The clutch worked we					

Tester reports – Started readily from cold & hot. The motor ran very well pulling strongly from low revs. The clutch worked well. All the gears selected & functioned normally. Both the period brakes worked with the rear being better than the front. The bike steered & handled nicely. A solid machine that was very pleasant on the road test.

Notes: -

<sup>1.</sup> This report is only the opinion of the tester on the day and should only be considered as a rough guide as time does not permit an in depth report. Antique machines will always require ongoing work.

<sup>2.</sup> All antique machines must be thoroughly checked over & fully serviced by a competent mechanic before any use, due to their age & the length of time that they may have been stored.

WWW.ROSPA.com recommends tyres that have been in storage for over 6 years or in use for 10 years should be replaced. For further information on tyre safety visit the ROSPA website page at <a href="http://www.rospa.com/roadsafety/adviceandinformation/vehiclesafety/tyresafet

<sup>4.</sup> The speedometer (if fitted) reading shown in this report is not necessarily an indication of the machines true mileage.

<sup>5.</sup> We strongly recommend that all Flat tank motorcycles are run on Ethanol Free petrol, such as Aspen or Avgas.